

MASKING TAPE

GENERAL PURPOSE MASKING TAPE

GECO®

GECO MASKING TAPE

GECO Masking Tapes are designed for masking variety of substrates in painting, carpentry and construction works. It gives good adhesion and release without leaving residues or impressions.

Features



INSTANT ADHESION



EASY TEAR



RESIDUE FREE



GOOD HOLDING POWER



RESISTS LIFTING & CURLING

Areas of Application

- To cover specific body areas that should stay free of sealants, adhesives, paints, etc.
- Commercial and residential painting, and construction
- Industrial masking, holding & packaging

Product Specification

Property	Type	Colour
Backing	Crepe Paper	Beige
Adhesive	Rubber	Clear



For more information, please visit www.geco.build.



Technical Specification

Tape Thickness	Approx. 0.13 mm
Temperature range	Long term: 0°C to 35°C Short term: 60°C (30 minutes)
Tensile Strength	7 kg/25 mm according to PSTC at 23°C ± 2°C
Elongation	16~24% according to PSTC at 23°C ± 2°C
Peel Strength	5 N/25 mm on steel according to DIN EN 1939:1996 at 23°C ± 2°C

Shelf Life & Storage

Shelf life is 12 months from the date of manufacturing, if stored in unopened and original packaging. Store in dry place away from direct sunlight.



Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.